

VL-100(T)

Med og uden touch



All-in-One Android

Hærdet glas og metalkabinnet

Tablet look

Den stilfulde kant-til-kant glasflade, de afrundede hjørner, aluminiumsramme og den smalle sorte kant giver et fængslende tablet-lignende udtryk.

En robust enhed, der på elegant vis, fremhæver produkter og andet materiale som vises på skærmen.



Ultra responsiv PCAP

Kun på touch modellen

Plasma belægning på skærmen

Speciel belægning gør glasfronten mere modstandsdygtig over for fingeraftryk og skaber en mere smidig bevægelse henover skærmen.



Optimal følsomhed
og hurtig respons



IPS-display

Flotte farver og naturtro farvedybde.
Bred betragtningsvinkel på 178°.



24/7 i 70.000 timer

Omkostningseffektiv og
designet til kontinuerlig brug
i op til 70.000 timer

Ideel til integration

Monteringsbeslag med mikrojustering og flush-fit overfladeintegration medfølger uden ekstra omkostninger
Kan monteres i de fleste kiosker, borde og skabe.



Specifikationer

		22"
Display	Resolution/Aspect Ratio	1920x1080 / 16:9
	Display Area (mm)	475x26.4
	Brightness (cd/m2)	250
	Color	16.7M
	Viewing Angle	178°
	Contrast Ratio	1500:1
Touch	Touch Technology	Projected Capacitive - 10 points (Only VL-100T)
	Glass Hardness	7H minimum
Audio	Speaker Type	2W, 5Ω (x2)
AV Inputs	Inputs	HDMI, USB
Power	Power Consumption (W)	21W
	Input Voltage	AC220V
Mechanical	Unit Size (WxHxD mm)	329x537x52
	Package Size (WxHxD mm)	663x455x178
	VESA Holes (mm)	100x100
	Net Weight (kg)	6
	Gross Weight (kg)	8

Specifikationer

22"

Computer	Video Formats	MPG, AVI, MP4, RM, RMVB, TS FHD 60FPS H.264/H.265 video encoding
	Audio/Image Formats	Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG)
	Media Resolution	1920x1080/1080x1920
	CPU	RK3568 64bit Cortex-A55 Quad @2GHz
	GPU	Quad Mali-G52 2EEDDR3 2GB
	RAM	4GB eMMC
	Internal Storage	32GB
	USB	1 x USB (OTG/HOST), 1 x USB (HOST)
	LAN	100M/1000M Ethernet
	Wi-Fi	802.11b/g/n/ac
	Optional 4G Module	1 x SIM Slot (optional)
	Bluetooth	5.0
	OS	Android 14
	Graphic Engine	OpenGL ES 1.1/2.0/3.2, OpenCL 2.0 and Vulkan 1.1
Environmental	Operating Temperature	0 °C to 50 °C
	Storage Temperature	-30°C to 60°C
	Operating Humidity	10% to 80%
	Storage Humidity	5% to 95%
Accessories	Included	Wall Mount, Remote Control, User Manual, Power Cable, USB to USB Cable, Wi-Fi Aerial
	Optional	Floor Stand/Trolley, Ceiling Mount, Table Stand